

# Pool Pro DPD #3 Tablets POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)

Chemwatch: 88-0802 Version No: 6.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Pool Pro DPD #3 Tablets
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Testing of Pools and Spas. Use according to manufacturer's directions.
--------------------------	---

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)
Address	10-12 Cairns Street Loganholme QLD 4129 Australia
Telephone	+61 7 3209 7884
Fax	+61 7 3209 8635
Website	http://www.poolpro.com.au/
Email	office@poolpro.com.au

## Emergency telephone number

Association / Organisation	ІХОМ
Emergency telephone numbers	+61 3 9663 2130 (International) (24 hours)
Other emergency telephone numbers	+61 1800 033 111

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Sensitisation (Respiratory) Category 1, Reproductive Toxicity Category 2	
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

#### Label elements

Hazard pictogram(s)	
Signal word	Danger

# Hazard statement(s)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Chemwatch Hazard Alert Code: 2

Issue Date: 06/12/2022 Print Date: 06/12/2022 L.GHS.AUS.EN.E

# Pool Pro DPD #3 Tablets

 H334
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 H361d
 Suspected of damaging the unborn child.

# Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P261	Avoid breathing dust/fumes.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P284	[In case of inadequate ventilation] wear respiratory protection.	
P264	Wash all exposed external body areas thoroughly after handling.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

#### Precautionary statement(s) Response

• • • • •	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

#### Precautionary statement(s) Storage

Store locked up.

# Precautionary statement(s) Disposal

P501

P405

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
7681-11-0	<50	potassium iodide
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

# **SECTION 4 First aid measures**

Description of first aid measures		
Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>	
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>	
Inhalation H If fumes, aerosols or combustion products are inhaled remove from contaminated area.     Other measures are usually unnecessary.		
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>	

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Firefighting measures**

#### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

Advice	for	firefighters
--------	-----	--------------

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>Decomposition may produce toxic fumes of: hydrogen iodide</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	Not Applicable

# SECTION 6 Accidental release measures

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

and material for containing ap			
Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing dust and contact with skin and eyes.</li> <li>Wear protective clothing, gloves, safety glasses and dust respirator.</li> <li>Use dry clean up procedures and avoid generating dust.</li> <li>Sweep up, shovel up or</li> <li>Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).</li> <li>Place spilled material in clean, dry, sealable, labelled container.</li> </ul>		
Major Spills	<ul> <li>Moderate hazard.</li> <li>CAUTION: Advise personnel in area.</li> <li>Alert Emergency Services and tell them location and nature of hazard.</li> <li>Control personal contact by wearing protective clothing.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Recover product wherever possible.</li> <li>IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.</li> <li>ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.</li> <li>If contamination of drains or waterways occurs, advise Emergency Services.</li> </ul>		

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe handling	
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>1000 tablets.</li> <li>Polyethylene or polypropylene container.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

# Page 4 of 9 Pool Pro DPD #3 Tablets

# **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits	(OEL)

# INGREDIENT DATA

# Not Available

# Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
potassium iodide	1.3 mg/m3	15 mg/m3		87 mg/m3
Ingredient	Original IDLH		Revised IDLH	
potassium iodide	Not Available		Not Available	
Occupational Exposure Banding				
Ingredient	Occupational Exposure Band Rating		Occupational Exposure Band Limit	
potassium iodide	E		≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the			

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

# MATERIAL DATA

#### Exposure controls

Appropriate engineering       Type of Contaminant:       Air Speed:         solvent, vapoura, degressing etc., evaporating from tark (in still air).       0.25-0.5 m/s         concols, furnes from pouring operations, intermittent container filing, low speed droweyer transfers, welding, spray       0.5-1 m/s (100-200 //min.)         dift, plating acid furnes, ipckling (elasaed at low velocity into zone of active generation)       0.5-1 m/s (200-500 //min.)         generation into zone of rapid air motion).       1.25 m/s (200-500 //min.)         grinding, abraive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of rapid air motion).       2.5-10 m/s (300-2000 //min.)         grinding, abraive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of 2.2 m/s (200-2000 //min.)       2.5-10 m/s (300-2000 //min.)         Within each range the appropriate value depends on:       1.0 bear in corrents minimal of revourable to capture       1.0 blauting room air currents         2. Contaminants of low toxicity or of nuisance value only.       2. Contaminants of low toxicity or of nuisance value only.       2. Contaminants of low toxicity generally decreases         with the square of distance from the currents minimal or favourable to capture.       3. High production, heavy use       4. Large hood or large air mass in motion       4. Sender (200-600 //min.)         Singe freency totoly falls rapidly with distance wavey from the copening of a simple extraction point. Orbot menchanical considerations, producing p		Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.			
Appropriate engineering control       g0-100 //min.)       g0-100 //min.)         dift, plating add mes, pickling (released to welcody into zone of active generation)       0.5-1 m/s (100-200 //min.)         generation into zone of rapid all motion)       2.5-10 m/s (200-500 //min.)         generation into zone of the ange       1.2.5 m/s (200-500 //min.)         grinding, abraive biasting, tumbing, high speed wheel generated dusts (released at high initial velocity into zone of 2.5-10 m/s (500-2000 f/min.)         Within each range the appropriate value depends on:       2.5-10 m/s (500-2000 f/min.)         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range       1.5 Dot within ach range the appropriate value depends on:         Lower end of the range theory shows that ai ruleoity into isot within the straction point. Collecal control only         Sintle theory shows that ai ruleoity into isot walue only.       2. Contaminants of low toxicity or of sintle extraction point. Other mechanical considerations, producing performance deficits within the straction appartume, should be ranking and m		Type of Contaminant:		Air Speed:	
Appropriate engineering controls       drift, plating acid fumes, pickling (released at low velocity into zone of acitve generation)       f/rmin.)         drift, plating acid fumes, pickling (released at low velocity into zone of acitve generation)       f/rmin.)         griene ration into zone of radip air motion)       grienting, conveyer loading, crusher dusts, gas discharge (active generation into zone of radip air motion)       2.5 r10 m/s (go0-2000 f/min.)         grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of wry high rapid air motion).       2.5 r10 m/s (go0-2000 f/min.)         Within each range the appropriate value depends on:		solvent, vapours, degreasing etc., evaporating from tank (in	n still air).		
Personal protection					
Very high rapid air motion).       (500-2000 t/min.)         Within each range the appropriate value depends on:       Lower end of the range       Upper end of the range         1: Room air currents minimal or favourable to capture       1: Disturbing room air currents         2: Contaminants of low toxicity or of nuisance value only.       2: Contaminants of high toxicity         3: Intermittent, low production.       3: High production, heavy use         4: Large hood or large air mass in motion       4: Small hood-local control only         Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point, for example, should be a minimum of 1-2 m/s (200-400 t/min) for extraction of solvents generated in a tak 2 meters distant from the extraction point. Note mechanical considerations, producing performance deficits within the extraction papartus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       • Safety glasses with side shields.         • Comical tensors may poe a special hazard; soft contact lenses may absorb and concentrate inflants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemical is used and and concentrate inflants. A written policy document, describing the wearing of lenses or restrictions on use, should be cren	controls		conveyer loading, crusher dusts, gas discharge (active		
Lower end of the range       Upper end of the range         1: Room air currents minimal or favourable to capture       1: Disturbing room air currents         2: Contaminants of low toxicity or of nuisance value only.       2: Contaminants of high toxicity         3: Intermittent, low production.       3: High production, heavy use         4: Large hood or large air mass in motion       4: Small hood-local control only         Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the contaminating source. The air velocity at the extraction pipe. Velocity generally decreases with the square of distance from the contaminating source. The air velocity at the extraction pipe. Velocity generally decreases with the square of distance from the contaminating source. The air velocity at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Very glasses with side shields.         . Safety glasses with side shields.       . Comical goggies.         . Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the waring of lenses or restrictions on use, should be created for eacel of restract. This should include a review of lens assorption in da docopytion for the class of chemicals in use and an account of injury experience. Medical and fities depersonnel should be removed in heir removal and			nerated dusts (released at high initial velocity into zone of		
Image: Protection       Image: Protection       Image: Protection       Image: Protection         Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection         Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection         Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection         Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Protection       Image: Pro		Within each range the appropriate value depends on:			
2: Contaminants of low toxicity or of nuisance value only.       2: Contaminants of high toxicity         3: Intermittent, low production.       3: High production, heavy use         4: Large hood or large air mass in motion       4: Small hood-local control only         Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction point. Other mechanical considerations, producing performance distance from the extraction point (in simple cases). Therefore the air speed at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Image: Comparison of the contaminating source. The air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Eye and face protection       Safety glasses with side shields.         Commical protection       Comparison on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be reasted for each workplace or task. This should include a review of lens absorption and account of unjury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be reasted for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of linjury experience. Medical and first-aid personnel should be		Lower end of the range	Upper end of the range		
3: Intermittent, low production.       3: High production, heavy use         4: Large hood or large air mass in motion       4: Small hood-local control only         Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the extraction apparatus, make it evelocity at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction point option the mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Safety glasses with side shields.         Eye and face protection       Safety glasses with side shields.         Chemical goggles.       Contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or estrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]		1: Room air currents minimal or favourable to capture	1: Disturbing room air currents		
4: Large hood or large air mass in motion       4: Small hood-local control only         Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Image: the system set is the shields.         Eye and face protection       Safety glasses with side shields.         Chemical goggles.       Contact lenses may base a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in the irremoval and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as son as pracicable. Lens should be removed at the first signs of eye redness or instration - lens should be trained in the irremoval and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as son as pracicable. Lens should be removed at the first signs of eye redness or instration - lens should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately an		2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity		
Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Image: A the optimization of solven the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Eye and face protection       Image: A the optimization of the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in the ir removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and using the irremoval and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and networkers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]		3: Intermittent, low production. 3: High production, heavy use			
with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Image: the extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.         Personal protection       Image: the extraction oppint (in simple cases). The extraction oppint (in simple cases). The extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in the extraction point (in simple cases). The extraction point (in simple cases).         Personal protection       Image: the extraction of solvents generated in the extraction optic (in the extraction point (in simple cases)). Therefore, the extraction point (in simple cases). The extraction optic (in the extraction point (in simple cases). The extractical performance (in the extraction point (in simple cases). The ext		4: Large hood or large air mass in motion	4: Small hood-local control only		
<ul> <li>Eye and face protection</li> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>		with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or			
<ul> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>	Personal protection				
Skin protection See Hand protection below	Eye and face protection	<ul> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or</li> </ul>			
	Skin protection	See Hand protection below			

Hands/feet protection	<ul> <li>NOTE:</li> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> <li>Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.</li> <li>polychloroprene.</li> <li>nitrile rubber.</li> <li>butyl rubber.</li> <li>butyl rubber.</li> <li>golyvinyl chloride.</li> <li>Gloves should be examined for wear and/ or degradation constantly.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>

# Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Pool Pro DPD #3 Tablets

POOL PTO DPD #3 Tablets

Material	CPI
NATURAL RUBBER	А
NATURAL+NEOPRENE	А
NITRILE	A

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

 The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

 Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

Use approved positive flow mask if significant quantities of dust becomes airborne.
 Try to avoid creating dust conditions.

#### **SECTION 9** Physical and chemical properties

Information on basic physical and chemical properties

information on basic physical and chemical properties				
Appearance	White solid tablets with no odour; miscible with water. White			
Physical state	Solid	Relative density (Water = 1)	Not Applicable	
Odour	No Odour	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable	
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable	
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	Not Applicable	Taste	Not Available	
Evaporation rate	Not Applicable	Explosive properties	Not Available	
Flammability	Not Applicable	Oxidising properties	Not Available	

Continued...

# Pool Pro DPD #3 Tablets

Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	5-7 (1 tablet in 10ml water)
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

# SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

#### Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.	
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.	
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.	
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.	
Chronic	<ul> <li>(conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</li> <li>Practical evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a substantial number of individuals at a greater frequency than would be expected from the response of a normal population.</li> <li>Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.</li> <li>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.</li> <li>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.</li> <li>Substances than can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsive to substances that can cause occupational asthma and people with pre-existing air-way hyper-responsive escore that can cause occupational asthma and there this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming</li></ul>	
	ΤΟΧΙΟΙΤΥ	IRRITATION
Pool Pro DPD #3 Tablets	Not Available	Not Available
	тохісіту	IRRITATION
potassium iodide	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>

Oral (Rat) LD50; 2500 mg/kg<sup>[1]</sup>

Skin: no adverse effect observed (not irritating)<sup>[1]</sup>

## Pool Pro DPD #3 Tablets

	<ol> <li>Value obtained from Europe ECHA Registered Sub specified data extracted from RTECS - Register of To</li> </ol>		ined from manufacturer's SDS. Unless otherwise
POTASSIUM IODIDE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: t distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposi person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens). Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bron asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type;		or Quincke's oedema. The pathogenesis of contact ner allergic skin reactions, e.g. contact urticaria, t simply determined by its sensitisation potential: the A weakly sensitising substance which is widely h which few individuals come into contact. From a more than 1% of the persons tested. onjunctivitis, are mostly the result of reactions of the anifestation of the immediate type. In addition to the he exposure period and the genetically determined itivity of the mucosa may play a role in predisposing a ctions or exposure to irritant substances.
	Particular attention is drawn to so-called atopic diathe asthma and atopic eczema (neurodermatitis) which is Exogenous allergic alveolitis is induced essentially by	associated with increased IgE synthe allergen specific immune-complexes	esis. of the IgG type; cell-mediated reactions (T
Acute Toxicity	Particular attention is drawn to so-called atopic diathe asthma and atopic eczema (neurodermatitis) which is Exogenous allergic alveolitis is induced essentially by	associated with increased IgE synthe allergen specific immune-complexes	esis. of the IgG type; cell-mediated reactions (T
Acute Toxicity Skin Irritation/Corrosion	Particular attention is drawn to so-called atopic diathe asthma and atopic eczema (neurodermatitis) which is Exogenous allergic alveolitis is induced essentially by lymphocytes) may be involved. Such allergy is of the	associated with increased IgE synthe allergen specific immune-complexes delayed type with onset up to four hou	esis. of the IgG type; cell-mediated reactions (T urs following exposure.
Skin Irritation/Corrosion	Particular attention is drawn to so-called atopic diathe asthma and atopic eczema (neurodermatitis) which is Exogenous allergic alveolitis is induced essentially by lymphocytes) may be involved. Such allergy is of the o	associated with increased IgE synthe allergen specific immune-complexes delayed type with onset up to four hou Carcinogenicity	esis. of the IgG type; cell-mediated reactions (T Irs following exposure.
	Particular attention is drawn to so-called atopic diathe asthma and atopic eczema (neurodermatitis) which is Exogenous allergic alveolitis is induced essentially by lymphocytes) may be involved. Such allergy is of the	associated with increased IgE synthe allergen specific immune-complexes delayed type with onset up to four hou Carcinogenicity Reproductivity	esis. of the IgG type; cell-mediated reactions (T rrs following exposure.

# **SECTION 12 Ecological information**

	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available
Endpoint	Test Duration (hr)	Species	Value	Source
EC50(ECx)	48h	Crustacea	1.27mg/l	2
EC50	48h	Crustacea	1.27mg/l	2
LC50	96h	Fish	>100mg/l	2
Extracted from	1. IUCLID Toxicity Data 2. Europe ECH	A Registered Substances - Ecotoxicological In	formation - Aquatic Toxicity 4. l	US EPA,
	Available Endpoint EC50(ECx) EC50 LC50 Extracted from	Available     Not Available       Endpoint     Test Duration (hr)       EC50(ECx)     48h       EC50     48h       LC50     96h       Extracted from 1. IUCLID Toxicity Data 2. Europe ECH	Available     Not Available     Not Available       Endpoint     Test Duration (hr)     Species       EC50(ECx)     48h     Crustacea       EC50     48h     Crustacea       LC50     96h     Fish       Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Interview	Available     Not Available     Not Available     Available       Endpoint     Test Duration (hr)     Species     Value       EC50(ECx)     48h     Crustacea     1.27mg/l       EC50     48h     Crustacea     1.27mg/l

#### DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
potassium iodide	HIGH	HIGH

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
potassium iodide	LOW (LogKOW = 0.0436)
Mobility in soil	
Ingredient	Mobility
potassium iodide	

# **SECTION 13 Disposal considerations**

# Waste treatment methods

Product / Packaging disposal	<ul> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Bury residue in an authorised landfill.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
------------------------------	--

# **SECTION 14 Transport information**

# Page 8 of 9

#### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

## Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
potassium iodide	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
potassium iodide	Not Available
· · · · · · · · · · · · · · · · · · ·	

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

potassium iodide is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (potassium iodide)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## **SECTION 16 Other information**

Revision Date	06/12/2022
Initial Date	27/11/2017

#### SDS Version Summary

Version	Date of Update	Sections Updated
5.1	05/12/2022	Appearance, Instability Condition, Personal Protection (hands/feet)
6.1	06/12/2022	Appearance, Name

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List INUSL: NON-DOMESTIC SUBSTANCES LIST IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.