



Spa Pro Bromine Tablets

POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)

Chemwatch Hazard Alert Code: 3

Chemwatch: 11-32173

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 01/06/2018

Print Date: 05/06/2018

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Spa Pro Bromine Tablets
Synonyms	Not Available
Proper shipping name	OXIDISING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions. Spa disinfectant.
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)
Address	10-12 Cairns Street Loganholme QLD 4129 Australia
Telephone	+61 7 3209 7884
Fax	+61 7 3209 8635
Website	https://www.poolpro.com.au/
Email	office@poolpro.com.au

Emergency telephone number

Association / Organisation	IXOM
Emergency telephone numbers	+61 3 9663 2130 (International) (24 hours)
Other emergency telephone numbers	+61 1800 033 111

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	S5
Classification [1]	Oxidizing Solid Category 2, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogenicity Category 2, Acute Aquatic Hazard Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD **DANGER**

Hazard statement(s)

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.

H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P221	Take any precaution to avoid mixing with combustibles/organic material.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P220	Keep/Store away from clothing/organic material/combustible materials.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use water jets for extinction.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

Precautionary statement(s) Storage

P405	Store locked up.
------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
16079-88-2	>90	<u>1-bromo-3-chloro-5,5-dimethylhydantoin</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <p>Immediately hold eyelids apart and flush the eye continuously with running water.</p> <p>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</p> <p>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</p> <p>Transport to hospital or doctor without delay.</p> <p>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</p>
Skin Contact	<p>If skin or hair contact occurs:</p> <p>Immediately flush body and clothes with large amounts of water, using safety shower if available.</p> <p>Quickly remove all contaminated clothing, including footwear.</p> <p>Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</p> <p>Transport to hospital, or doctor.</p>
Inhalation	<p>If fumes or combustion products are inhaled remove from contaminated area.</p> <p>Lay patient down. Keep warm and rested.</p> <p>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</p> <p>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</p> <p>Transport to hospital, or doctor.</p> <p>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</p> <p>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</p> <p>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</p> <p>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</p> <p>This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)</p>

Ingestion

For advice, contact a Poisons Information Centre or a doctor at once.
 Urgent hospital treatment is likely to be needed.
If swallowed do NOT induce vomiting.
 If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 Observe the patient carefully.
 Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Excellent warning properties force rapid escape of personnel from chlorine vapour thus most inhalations are mild to moderate. If escape is not possible, exposure to high concentrations for a very short time can result in dyspnea, haemophysis and cyanosis with later complications being tracheobroncho-pneumonitis and pulmonary oedema. Oxygen, intermittent positive pressure breathing apparatus and aerosolised bronchodilators are of therapeutic value where chlorine inhalation has been light to moderate. Severe inhalation should result in hospitalisation and treatment for a respiratory emergency.

Any chlorine inhalation in an individual with compromised pulmonary function (COPD) should be regarded as a severe inhalation and a respiratory emergency. [CCINFO, Dow 1988]

Effects from exposure to chlorine gas include pulmonary oedema which may be delayed. Observation in hospital for 48 hours is recommended

Diagnosed asthmatics and those people suffering from certain types of chronic bronchitis should receive medical approval before being employed in occupations involving chlorine exposure.

If burn is present, treat as any thermal burn, after decontamination.

For acute or short term repeated exposures to strong acids:

Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.

Respiratory distress may require cricothyrotomy if endotracheal intubation is contraindicated by excessive swelling

Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.

Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.

INGESTION:

Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.

Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.

Charcoal has no place in acid management.

Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. **DO NOT use neutralising agents or any other additives.** Several litres of saline are required.

Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.

Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.

(ICSC24419/24421

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media****FOR SMALL FIRE:**

USE FLOODING QUANTITIES OF WATER.

DO NOT use dry chemical, CO₂, foam or halogenated-type extinguishers.

FOR LARGE FIRE

Flood fire area with water from a protected position

Special hazards arising from the substrate or mixture**Fire Incompatibility**

Avoid storage with reducing agents.

Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous

Advice for firefighters**Fire Fighting**

Alert Fire Brigade and tell them location and nature of hazard.

May be violently or explosively reactive.

Wear full body protective clothing with breathing apparatus.

Prevent, by any means available, spillage from entering drains or water courses.

Fight fire from a safe distance, with adequate cover.

Extinguishers should be used only by trained personnel.

Use water delivered as a fine spray to control fire and cool adjacent area.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected location.

If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard

Combustible.

Slight fire hazard when exposed to heat or flame.

Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.

Heating may cause expansion or decomposition leading to violent rupture of containers.

May emit acrid smoke and corrosive fumes.

Combustion products include:

carbon monoxide (CO)

,

carbon dioxide (CO₂)

,

hydrogen chloride

,

phosgene

,

nitrogen oxides (NO_x)

,

other pyrolysis products typical of burning organic material.

HAZCHEM

1W

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</p> <p>Check regularly for spills and leaks.</p> <p>Clean up all spills immediately.</p> <p>No smoking, naked lights, ignition sources.</p> <p>Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result.</p> <p>Avoid breathing dust or vapours and all contact with skin and eyes.</p> <p>Control personal contact with the substance, by using protective equipment.</p> <p>Contain and absorb spill with dry sand, earth, inert material or vermiculite.</p> <p>DO NOT use sawdust as fire may result.</p> <p>Scoop up solid residues and seal in labelled drums for disposal.</p> <p>Neutralise/decontaminate area.</p>
Major Spills	<p>Clear area of personnel and move upwind.</p> <p>Alert Fire Brigade and tell them location and nature of hazard.</p> <p>May be violently or explosively reactive.</p> <p>Wear full body protective clothing with breathing apparatus.</p> <p>Prevent, by any means available, spillage from entering drains or water courses.</p> <p>No smoking, flames or ignition sources.</p> <p>Increase ventilation.</p> <p>Contain spill with sand, earth or other clean, inert materials.</p> <p>NEVER USE organic absorbents such as sawdust, paper or cloth.</p> <p>Use spark-free and explosion-proof equipment.</p>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<p>Avoid personal contact and inhalation of dust, mist or vapours.</p> <p>Provide adequate ventilation.</p> <p>Always wear protective equipment and wash off any spillage from clothing.</p> <p>Keep material away from light, heat, flammables or combustibles.</p> <p>Keep cool, dry and away from incompatible materials.</p> <p>Avoid physical damage to containers.</p> <p>DO NOT repack or return unused portions to original containers. Withdraw only sufficient amounts for immediate use.</p> <p>Use only minimum quantity required.</p> <p>Avoid using solutions of peroxides in volatile solvents.</p> <p>Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)</p> <p>Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.</p> <p>Establish good housekeeping practices.</p> <p>Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.</p> <p>Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.</p> <p>Do not use air hoses for cleaning.</p> <p>Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area.</p>
Other information	<p>Store in original containers.</p> <p>Keep containers securely sealed as supplied.</p> <p>Store in a cool, well ventilated area.</p> <p>Keep dry.</p> <p>Store under cover and away from sunlight.</p> <p>Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction.</p> <p>Store away from incompatible materials and foodstuff containers.</p> <p>DO NOT stack on wooden floors or pallets.</p> <p>Protect containers from physical damage.</p> <p>In addition, Goods of Class 5.1, packing group II should be:</p> <ul style="list-style-type: none"> stored in piles so that the height of the pile does not exceed 1 metre the maximum quantity in a pile or building does not exceed 1000 tonnes unless the area is provided with automatic fire extinguishers the maximum height of a pile does not exceed 3 metres where the room is provided with automatic fire extinguishers or 2 meters if not. the minimum distance between piles is not less than 2 metres where the room is provided with automatic fire extinguishers or 3 meters if not. the minimum distance to walls is not less than 1 metre.

Conditions for safe storage, including any incompatibilities

Suitable container	<p>DO NOT repack. Use containers supplied by manufacturer only.</p> <p>For low viscosity materials</p> <ul style="list-style-type: none"> Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. <p>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids:</p> <ul style="list-style-type: none"> Removable head packaging and cans with friction closures may be used. - Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *. - In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *.
---------------------------	---

	- * unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. 1kg, 2kg,4kg,10kg,20kg, 25kg
Storage incompatibility	Contact with acids produces toxic fumes Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous Segregate from alcohol, water. Avoid strong bases. Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent. Avoid storage with reducing agents.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
1-bromo-3-chloro-5,5-dimethylhydantoin	Bromo-3-chloro-5,5-dimethylhydantoin, 1-; (1-Bromo-3-chloro-5,5-dimethyl-2,4-imidazolidinedione)	4.2 mg/m3	46 mg/m3	280 mg/m3
Ingredient	Original IDLH	Revised IDLH		
1-bromo-3-chloro-5,5-dimethylhydantoin	Not Available	Not Available		

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.</p> <p>Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.</p> <p>If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.</p>
Personal protection	
Eye and face protection	<p>Chemical goggles.</p> <p>Full face shield may be required for supplementary but never for primary protection of eyes.</p> <p>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</p>
Skin protection	See Hand protection below
Hands/feet protection	<p>Wear chemical protective gloves, e.g. PVC.</p> <p>Wear safety footwear or safety gumboots, e.g. Rubber</p> <p>NOTE:</p> <p>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</p> <p>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</p> <p>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</p> <p>DO NOT wear cotton or cotton-backed gloves.</p> <p>DO NOT wear leather gloves.</p> <p>Promptly hose all spills off leather shoes or boots or ensure that such footwear is protected with PVC over-shoes.</p>
Body protection	See Other protection below
Other protection	<p>Overalls.</p> <p>PVC Apron.</p> <p>PVC protective suit may be required if exposure severe.</p> <p>Eyewash unit.</p> <p>Ensure there is ready access to a safety shower.</p> <p>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</p> <p>For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</p> <p>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</p>

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures. The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
Use approved positive flow mask if significant quantities of dust becomes airborne.
Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	White to off white tablet with faint halogen odour; miscible with water.		
Physical state	Divided Solid	Relative density (Water = 1)	0.9
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	160	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable under normal handling conditions. Prolonged exposure to heat. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	Chlorine vapour is extremely irritating to the airways and lungs, causing coughing, choking, breathing difficulty, chest pain, headache, vomiting, fluid accumulation in the lungs, chest infection and loss of consciousness. Effects may be delayed. Long term exposure (at workplace) may lead to corrosion of the teeth, irritate the linings of the nose and may increase the likelihood of developing tuberculosis. Recent studies have not confirmed these findings. Very low concentrations may irritate the eyes, nose and throat and cause the above reactions. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
Skin Contact	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.
Eye	The material can produce chemical burns following direct contact with the skin. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Solution of material in moisture on the skin, or perspiration, may markedly increase skin corrosion and accelerate tissue destruction Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.

Chronic

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Based on experience with similar materials, there is a possibility that exposure to the material may reduce fertility in humans at levels which do not cause other toxic effects.

Chronic poisoning from ionic bromides has historically resulted from medical use of bromides but not from exposure in the environment or workplace. In the absence of other signs of poisoning, there may be depression, hallucinations and schizophrenia-like psychosis. Bromides may also cause sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness, inability to speak, difficulty speaking, weakness, fatigue, a spinning sensation, stupor, coma, decreased appetite, nausea, vomiting, an acne-like rash on the face (bronchoderma), legs and trunk, swelling of the bronchi and a profuse discharge from the nostrils. There may also be inco-ordination and very brisk reflexes. Correlation of nervous system symptoms with blood levels of bromide is inexact. Current day usage of bromides is generally limited to antihistamines such as brompheniramine, which is a covalent compound; ionic compounds are no longer regularly used due to their toxicity.

In test animals, brominated vegetable oils (BVOs), historically used as emulsifiers in certain soda-based soft drinks, produced damage to the heart and kidneys in addition to increasing fat deposits in these organs. In extreme cases, BVOs caused testicular damage, stunted growth and produced lethargy and fatigue.

Brominism (chronic bromine poisoning) produces slurred speech, apathy, headache, decreased memory, anorexia and drowsiness, psychosis resembling paranoid schizophrenia, and personality changes.

Several cases of foetal abnormalities have been described in mothers who took large doses of bromides during pregnancy. Reduced breathing capacity may result from chronic low level exposure to chlorine gas. Chronic poisoning may result in cough, severe chest pains, sore throat and blood in the phlegm. Moderate to severe exposures over 3 years produced decreased lung capacity in a number of workers.

Delayed effects can include shortness of breath, violent headaches, lung swelling and pneumonia.

Chloralkali workers exposed over many years showed fatigue, and a modest increase in anxiety and dizziness. There may be an increase in white blood cell and decrease in red blood cell count.

Spa Pro Bromine Tablets	TOXICITY	IRRITATION
	Not Available	Not Available
1-bromo-3-chloro-5,5-dimethylhydantoin	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Primary Skin Irritation Index 6.1
	Oral (rat) LD50: 1390 mg/kg ^[2]	Skin (rabbit): SEVERE **
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

1-BROMO-3-CHLORO-5,5-DIMETHYLHYDANTOIN

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

No significant acute toxicological data identified in literature search.

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

for halohydantoins

Acute toxicity: The halohydantoins were shown to be of low toxicity by the oral and dermal routes of exposure. Acute toxicity by the inhalation route is more significant. The halohydantoins are significant eye and skin irritants. Dermal sensitization has also been observed for some of the halohydantoin compounds.

Non-acute toxicity testing of halohydantoins and their breakdown products dimethylhydantoin and ethylmethylhydantoin (DMH/EMH) (including sub chronic, developmental, reproductive, and chronic toxicity testing) all show the presence of non-specific toxicity only at relatively high doses of the test chemical. The primary reason for developing generic data on DMH and EMH rather than the entire halohydantoin molecule is that these ring structures represent the persistent component of the halohydantoins. A secondary reason for evaluating the halohydantoin moieties is that the corrosive properties of the released halogens would limit the amount of chemical that could be administered to laboratory animals; thereby precluding a meaningful evaluation of the halohydantoin moieties

Developmental and reproductive toxicity data demonstrate no increase in susceptibility to the toxic effects of 5,5-dimethylhydantoin with the exception of one study, where foetal and litter effects (increased incidence of 27th presacral vertebrae) in rabbits were observed at a lower dose level than that which resulted in maternal toxicity (decreased body weight and food consumption during the dosing period) following treatment. The increase of 27th presacral vertebrae is a common variation found in rabbit developmental toxicity studies and was not considered an adverse effect. In a prenatal developmental toxicity study conducted in rabbits with 5-ethyl-5-methylhydantoin, there was no increased susceptibility of the foetuses observed.

Available metabolism data indicate that DMH and EMH are excreted unchanged in the rat.

Positive sensitiser in guinea pig skin assay ** * [Farm Chem. Handbook] ** Red for Halohydantoins

Acute Toxicity	Carcinogenicity
Skin Irritation/Corrosion	Reproductivity
Serious Eye Damage/Irritation	STOT - Single Exposure
Respiratory or Skin sensitisation	STOT - Repeated Exposure
Mutagenicity	Aspiration Hazard

Legend:

- Data available but does not fill the criteria for classification
- Data available to make classification
- Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Spa Pro Bromine Tablets	Not Available	Not Available	Not Available	Not Available	Not Available
1-bromo-3-chloro-5,5-dimethylhydantoin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.14mg/L	4
	EC50	48	Crustacea	0.4mg/L	4

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Chlorine:

Atmospheric Fate: Atmospheric chlorine forms hydrochloric or hypochlorous acid in the atmosphere, either through reactions with hydroxyl radicals or, other trace species, such as hydrocarbons. These acids are believed to be removed from the atmosphere primarily through precipitation washout/dry deposition. When chlorine, hypochlorous acid or hydrogen chloride mixes in the atmosphere with water vapor, dilute solutions of strong mineral acids form which fall to earth as acid rain, snow, fog, or acidified dry particles.

Terrestrial Fate: Soil - Chlorine may react with soil components to form chlorides; depending on their water solubility, these chlorides are easily washed out from the soil. Plants - Vegetation acts as an important artificial reservoir, (sink), for chlorine air pollution. Elevated levels of chlorine can cause plant injury; however chlorine tends to be rapidly converted to other less toxic forms. Chlorine is toxic to plant growth, however; it is also essential to plant growth - crops need around 2 kg or more of chlorine per acre. Acute toxicity is characterized by defoliation, with no leaf symptoms and, in higher plant forms, by spotting of the leaves.

Aquatic Fate: Water chlorination initially introduces chlorine into the water as chlorine gas, hypochlorite ion, or its salt. Chlorine in aqueous systems evaporates, or quickly decays, to residual forms, such as hypochlorous acid, chloramine and/or chlorinated organics.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1-bromo-3-chloro-5,5-dimethylhydantoin	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
1-bromo-3-chloro-5,5-dimethylhydantoin	LOW (LogKOW = -0.9441)

Mobility in soil

Ingredient	Mobility
1-bromo-3-chloro-5,5-dimethylhydantoin	LOW (KOC = 23.14)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<p>Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible.</p> <p>Otherwise:</p> <p>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</p> <p>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</p> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> Reduction Reuse Recycling Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.</p> <p>DO NOT allow wash water from cleaning or process equipment to enter drains.</p> <p>It may be necessary to collect all wash water for treatment before disposal.</p> <p>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</p> <p>Where in doubt contact the responsible authority.</p> <p>Recycle wherever possible.</p> <p>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</p> <p>Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurring in water; Neutralisation with soda-lime or soda-ash followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)</p> <p>Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.</p> <p>For small quantities of oxidising agent:</p> <p>Cautiously acidify a 3% solution to pH 2 with sulfuric acid.</p> <p>Gradually add a 50% excess of sodium bisulfite solution with stirring.</p> <p>Add a further 10% sodium bisulfite.</p> <p>If no further reaction occurs (as indicated by a rise in temperature) cautiously add more acid.</p>
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

	 
Marine Pollutant	
HAZCHEM	1W

Land transport (DOT)

UN number	3085				
UN proper shipping name	OXIDISING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)				
Transport hazard class(es)	<table border="1"> <tr> <td>Class</td> <td>5.1</td> </tr> <tr> <td>Subrisk</td> <td>8</td> </tr> </table>	Class	5.1	Subrisk	8
Class	5.1				
Subrisk	8				
Packing group	II				
Environmental hazard	Environmentally hazardous				
Special precautions for user	<table border="1"> <tr> <td>Special provisions</td> <td>274</td> </tr> <tr> <td>Limited quantity</td> <td>1 kg</td> </tr> </table>	Special provisions	274	Limited quantity	1 kg
Special provisions	274				
Limited quantity	1 kg				

Air transport (ICAO-IATA / DGR)

UN number	3085														
UN proper shipping name	Oxidizing solid, corrosive, n.o.s. * (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)														
Transport hazard class(es)	<table border="1"> <tr> <td>ICAO/IATA Class</td> <td>5.1</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>8</td> </tr> <tr> <td>ERG Code</td> <td>5C</td> </tr> </table>	ICAO/IATA Class	5.1	ICAO / IATA Subrisk	8	ERG Code	5C								
ICAO/IATA Class	5.1														
ICAO / IATA Subrisk	8														
ERG Code	5C														
Packing group	II														
Environmental hazard	Environmentally hazardous														
Special precautions for user	<table border="1"> <tr> <td>Special provisions</td> <td>A3</td> </tr> <tr> <td>Cargo Only Packing Instructions</td> <td>562</td> </tr> <tr> <td>Cargo Only Maximum Qty / Pack</td> <td>25 kg</td> </tr> <tr> <td>Passenger and Cargo Packing Instructions</td> <td>558</td> </tr> <tr> <td>Passenger and Cargo Maximum Qty / Pack</td> <td>5 kg</td> </tr> <tr> <td>Passenger and Cargo Limited Quantity Packing Instructions</td> <td>Y544</td> </tr> <tr> <td>Passenger and Cargo Limited Maximum Qty / Pack</td> <td>2.5 kg</td> </tr> </table>	Special provisions	A3	Cargo Only Packing Instructions	562	Cargo Only Maximum Qty / Pack	25 kg	Passenger and Cargo Packing Instructions	558	Passenger and Cargo Maximum Qty / Pack	5 kg	Passenger and Cargo Limited Quantity Packing Instructions	Y544	Passenger and Cargo Limited Maximum Qty / Pack	2.5 kg
Special provisions	A3														
Cargo Only Packing Instructions	562														
Cargo Only Maximum Qty / Pack	25 kg														
Passenger and Cargo Packing Instructions	558														
Passenger and Cargo Maximum Qty / Pack	5 kg														
Passenger and Cargo Limited Quantity Packing Instructions	Y544														
Passenger and Cargo Limited Maximum Qty / Pack	2.5 kg														

Sea transport (IMDG-Code / GGVSee)

UN number	3085						
UN proper shipping name	OXIDIZING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)						
Transport hazard class(es)	<table border="1"> <tr> <td>IMDG Class</td> <td>5.1</td> </tr> <tr> <td>IMDG Subrisk</td> <td>8</td> </tr> </table>	IMDG Class	5.1	IMDG Subrisk	8		
IMDG Class	5.1						
IMDG Subrisk	8						
Packing group	II						
Environmental hazard	Marine Pollutant						
Special precautions for user	<table border="1"> <tr> <td>EMS Number</td> <td>F-A , S-Q</td> </tr> <tr> <td>Special provisions</td> <td>274</td> </tr> <tr> <td>Limited Quantities</td> <td>1 kg</td> </tr> </table>	EMS Number	F-A , S-Q	Special provisions	274	Limited Quantities	1 kg
EMS Number	F-A , S-Q						
Special provisions	274						
Limited Quantities	1 kg						

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

1-BROMO-3-CHLORO-5,5-DIMETHYLHYDANTOIN(16079-88-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (1-bromo-3-chloro-5,5-dimethylhydantoin)
China - IECSC	Y

Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	01/06/2018
Initial Date	01/06/2018

Other information

Ingredients with multiple cas numbers

Name	CAS No
1-bromo-3-chloro-5,5-dimethylhydantoin	16079-88-2, 32718-18-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
PC – STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.