

FULL INVERTER HEAT PUMP

ENERGY
EFFICIENT

Swim All Year Round

with full inverter heating & cooling technology



8 Top Discharge Models

8 Side Discharge Models

Neptune
for swimming pools

X-PRO

SCAN FOR
MORE INFO



KEY FEATURES FOR ALL MODELS

- ✓ Full inverter technology saves you money and power, by intelligently adjusting its power consumption while maintaining your chosen requirements
- ✓ 2 - 3 times more efficient than standard heat pumps
- ✓ TurboSilence® inverter technology for super quiet operation
- ✓ 2-in-1 heating and cooling system
- ✓ Titanium heat exchanger
- ✓ Wi-Fi with smart functions
- ✓ Intuitive display with real-time power consumption data
- ✓ Marine grade anti-corrosion aluminium alloy casing
- ✓ 8 side discharge and 8 top discharge models
- ✓ Compatible with Neptune Heat Pump Controllers

OPERATING CONDITIONS

| Specification | | Range |
|---------------------|-------------------------|--------------|
| Operating Range | Ambient Air Temperature | -15°C – 43°C |
| Temperature Setting | Heating Capacity | 18°C – 40°C |
| | Cooling Capacity | 12°C – 30°C |

Neptune X-Pro Heat Pumps feature a revolutionary 2-in-1 heating and cooling system. Designed with a focus on energy efficiency, the X-Pro range offers a quiet, durable and easy to use solution ideal for those who prioritise reliability and efficiency.

Experience total control with a real-time power consumption display and an intuitive interface offering customisable settings and data at your fingertips. Seamlessly connect to Wi-Fi for smart functionality, making comfort management effortless.



TECHNICAL DATA - SIDE DISCHARGE

| Model | NHX10 | NHX13 | NHX17 | NHX21 | NHX26 | NHX32 | NHX323 | NHX403 |
|------------------------------------|--------------------------|---------------|---------------|---------------|----------------|----------------|---------------------|----------------|
| Advised Pool Volume (L) | 20,000-40,000 | 25,000-50,000 | 30,000-60,000 | 40,000-75,000 | 55,000-100,000 | 65,000-120,000 | 65,000-120,000 | 90,000-160,000 |
| Heating Capacity (kW) ^A | 10.2 | 13.2 | 16.8 | 21.0 | 25.5 | 31.5 | 31.5 | 40.0 |
| Power Supply | Single Phase, 230V, 50Hz | | | | | | 3 Phase, 400V, 50Hz | |
| Net Dimension LxWxH (mm) | 799x432x650 | 893x432x650 | 939x432x650 | 995x432x750 | 1125x429x952 | 1074x539x947 | 1074x539x947 | 1260x539x947 |
| Net Weight (kg) | 51 | 61 | 65 | 70 | 98 | 102 | 111 | 126 |

TECHNICAL DATA - TOP DISCHARGE

| Model | NHX10TD | NHX13TD | NHX17TD | NHX21TD | NHX26TD | NHX32TD | NHX32TD3 | NHX40TD3 |
|------------------------------------|--------------------------|---------------|---------------|---------------|----------------|----------------|---------------------|----------------|
| Advised Pool Volume (L) | 20,000-40,000 | 25,000-50,000 | 30,000-60,000 | 40,000-75,000 | 50,000-100,000 | 65,000-120,000 | 65,000-120,000 | 90,000-160,000 |
| Heating Capacity (kW) ^A | 10.2 | 13.2 | 17.2 | 21.0 | 26.0 | 31.5 | 31.5 | 40.0 |
| Power Supply | Single Phase, 230V, 50Hz | | | | | | 3 Phase, 400V, 50Hz | |
| Net Dimension LxWxH (mm) | 710x753x668 | 710x753x668 | 710x775x668 | 710x775x668 | 710x775x743 | 729x955x917 | 729x955x917 | 845x955x917 |
| Net Weight (kg) | 61 | 66 | 71 | 78 | 102 | 110 | 117 | 141 |



AVAILABLE FROM YOUR
LOCAL POOL PRO STOCKIST



^AIn Turbo Mode, 26°C air & water temp & 80% humidity.
^{*}Warranty conditions apply.

PUMPS | FILTERS | CHLORINATORS | CLEANERS | UNDERWATER LIGHTS | HEATING | ACCESSORIES | CHEMICALS | SPA PRODUCTS | SPARE PARTS



Simply A Better Choice

Phone Free Call: 1800 143 788 International Phone: + 61 7 3209 7884
Email: office@poolpro.com.au Web: www.poolpro.com.au