

Spa Pro Bromine Tablets

POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)

Chemwatch: 11-32173 Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 01/06/2018 Print Date: 05/06/2018 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Spa Pro Bromine Tablets
Synonyms	Not Available
Proper shipping name	OXIDISING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)
Other means of identification	Not Available
Relevant identified uses of the	substance or mixture and uses advised against
Relevant identified uses	Use according to manufacturer's directions. Spa disinfectant.
Details of the supplier of the sa	afety data sheet
Registered company name	POPS Group (The POPS Group Pty Ltd as Trustee for The Pool Shops Trust)
Address	10-12 Cairns Street Loganholme QLD 4129 Australia
Telephone	+61 7 3209 7884
Fax	+61 7 3209 8635
Website	https://www.poolpro.com.au/
Email	office@poolpro.com.au
Emergency telephone number	
Association / Organisation	IXOM
Emergency telephone numbers	+61 3 9663 2130 (International) (24 hours)

SECTION 2 HAZARDS IDENTIFICATION

numbers

Other emergency telephone

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	S5
Classification ^[1]	Oxidizing Solid Category 2, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogenicity Category 2, Acute Aquatic Hazard Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)



+61 1800 033 111









SIGNAL	WORD

DANGER

Hazard statement(s)

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.

H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P221	Take any precaution to avoid mixing with combustibles/organic material.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P220	Keep/Store away from clothing/organic material/combustible materials.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use water jets for extinction.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
16079-88-2	>90	1-bromo-3-chloro-5,5-dimethylhydantoin

SECTION 4 FIRST AID MEASURES

Description of first aid measur	es
Eye Contact	If this product comes in contact with the eyes:
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)

For advice, contact a Poisons Information Centre or a doctor at once.

Urgent hospital treatment is likely to be needed.

If swallowed do **NOT** induce vomiting

If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent

Observe the patient carefully.

Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

aspiration

Excellent warning properties force rapid escape of personnel from chlorine vapour thus most inhalations are mild to moderate. If escape is not possible, exposure to high concentrations for a very short time can result in dyspnea, haemophysis and cyanosis with later complications being tracheobroncho-pneumonitis and pulmonary oedema. Oxygen, intermittent positive pressure breathing apparatus and aerosolysed bronchodilators are of therapeutic value where chlorine inhalation has been light to moderate.

Severe inhalation should result in hospitalisation and treatment for a respiratory emergency.

Any chlorine inhalation in an individual with compromised pulmonary function (COPD) should be regarded as a severe inhalation and a respiratory emergency. [CCINFO, Dow 1988]

Effects from exposure to chlorine gas include pulmonary oedema which may be delayed. Observation in hospital for 48 hours is recommended

Diagnosed asthmatics and those people suffering from certain types of chronic bronchitis should receive medical approval before being employed in occupations involving chloring exposure

If burn is present, treat as any thermal burn, after decontamination.

For acute or short term repeated exposures to strong acids:

Ingestion

Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.

Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.

Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury

Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.

Charcoal has no place in acid management.

Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.

Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.

Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.

(ICSC24419/24421

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

FOR SMALL FIRE:

USE FLOODING QUANTITIES OF WATER.

DO NOT use dry chemical, CO2, foam or halogenated-type extinguishers.

FOR LARGE FIRE

Flood fire area with water from a protected position

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid storage with reducing agents. Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous
Advice for firefighters	
Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water courses. Fight fire from a safe distance, with adequate cover. Extinguishers should be used only by trained personnel. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	Combustible. Slight fire hazard when exposed to heat or flame. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit acrid smoke and corrosive fumes. Combustion products include: carbon monoxide (CO) , carbon dioxide (CO2) , hydrogen chloride , phosgene , nitrogen oxides (NOx) , other pyrolysis products typical of burning organic material.
HAZCHEM	1W

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material Check regularly for spills and leaks. Clean up all spills immediately. No smoking, naked lights, ignition sources. Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result. **Minor Spills** Avoid breathing dust or vapours and all contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with dry sand, earth, inert material or vermiculite. DO NOT use sawdust as fire may result Scoop up solid residues and seal in labelled drums for disposal Neutralise/decontaminate area Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water courses. **Major Spills** No smoking, flames or ignition sources. Increase ventilation. Contain spill with sand, earth or other clean, inert materials. NEVER USE organic absorbents such as sawdust, paper or cloth. Use spark-free and explosion-proof equipment.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling	a
-------------------------------	---

Avoid personal contact and inhalation of dust, mist or vapours.

Provide adequate ventilation.

Always wear protective equipment and wash off any spillage from clothing.

Keep material away from light, heat, flammables or combustibles.

Keep cool, dry and away from incompatible materials.

Avoid physical damage to containers.

DO NOT repack or return unused portions to original containers. Withdraw only sufficient amounts for immediate use.

Use only minimum quantity required.

Avoid using solutions of peroxides in volatile solvents.

Safe handling

Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)

Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame

Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.

Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.

Do not use air hoses for cleaning.

Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area.

Store in original containers.

Keep containers securely sealed as supplied.

Store in a cool, well ventilated area.

Keep dry.

Store under cover and away from sunlight.

Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction.

Store away from incompatible materials and foodstuff containers.

DO NOT stack on wooden floors or pallets Other information

Protect containers from physical damage In addition, Goods of Class 5.1, packing group II should be:

stored in piles so that

the height of the pile does not exceed 1 metre

the maximum quantity in a pile or building does not exceed 1000 tonnes unless the area is provided with automatic fire extinguishers the maximum height of a pile does not exceed 3 metres where the room is provided with automatic fire extinguishers or 2 meters if not. the minimum distance between piles is not less than 2 metres where the room is provided with automatic fire extinguishers or 3 meters if not.

the minimum distance to walls is not less than 1 metre.

Conditions for safe storage, including any incompatibilities

DO NOT repack. Use containers supplied by manufacturer only.

For low viscosity materials

Drums and jerricans must be of the non-removable head type.

Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids: Removable head packaging and

Suitable container

cans with friction closures may be used

Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact

In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage

* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |1kg, 2kg,4kg,10kg,20kg,|25kg Contact with acids produces toxic fumes Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous Segregate from alcohol, water. Storage incompatibility Avoid strong bases Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent. Avoid storage with reducing agents.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

| EMERGENCY LIMITS

Ingredient	Material name		TEEL-1	TEEL-2	TEEL-3
1-bromo-3-chloro-5,5- dimethylhydantoin	Bromo-3-chloro-5,5-dimethylhydantoin, 1-; (1-Bromo-3-chloro-5,5-dimethyl-2,4-imidazolidinedione)		4.2 mg/m3	46 mg/m3	280 mg/m3
Ingredient	Original IDLH	Revised IDLH			
1-bromo-3-chloro-5,5- dimethylhydantoin	Not Available	Not Available			

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Appropriate engineering controls

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.

If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

Personal protection











Eve and face protection

Full face shield may be required for supplementary but never for primary protection of eyes.

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Hands/feet protection

Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

DO NOT wear cotton or cotton-backed gloves

DO NOT wear leather gloves

Promptly hose all spills off leather shoes or boots or ensure that such footwear is protected with PVC over-shoes.

Body protection

See Other protection below

Overalls. PVC Apron.

PVC protective suit may be required if exposure severe. Eyewash unit.

Other protection

Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static

For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).

Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection

Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White to off white tablet with faint halogen odour; miscible with water.			
Physical state	Divided Solid	Relative density (Water = 1)	0.9	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	160	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	Not Available	Taste	Not Available	
Evaporation rate	Not Available	Explosive properties	Not Available	
Flammability	Not Available	Oxidising properties	Not Available	
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable	
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available	
Vapour pressure (kPa)	Not Available	Gas group	Not Available	
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available	
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available	

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable under normal handling conditions. Prolonged exposure to heat. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

	Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Inhaled	Chlorine vapour is extremely irritating to the airways and lungs, causing coughing, choking, breathing difficulty, chest pain, headache, vomiting, fluid accumulation in the lungs, chest infection and loss of consciousness. Effects may be delayed. Long term exposure (at workplace) may lead to corrosion of the teeth, irritate the linings of the nose and may increase the likelihood of developing tuberculosis. Recent studies have not confirmed these findings. Very low concentrations may irritate the eyes, nose and throat and cause the above reactions. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.
Skin Contact	The material can produce chemical burns following direct contact with the skin. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Solution of material in moisture on the skin, or perspiration, may markedly increase skin corrosion and accelerate tissue destruction Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Based on experience with similar materials, there is a possibility that exposure to the material may reduce fertility in humans at levels which do not cause other toxic effects.

Chronic poisoning from ionic bromides has historically resulted from medical use of bromides but not from exposure in the environment or workplace. In the absence of other signs of poisoning, there may be depression, hallucinations and schizophrenia-like psychosis. Bromides may also cause sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness, inability to speak, difficulty speaking, weakness, fatigue, a spinning sensation, stupor, coma, decreased appetite, nausea, vomiting, an acne-like rash on the face (bronchoderma), legs and trunk, swelling of the bronchi and a profuse discharge from the nostrils. There may also be inco-ordination and very brisk reflexes. Correlation of nervous system symptoms with blood levels of bromide is inexact. Current day usage of bromides is generally limited to antihistamines such as brompheniramine, which is a covalent compound; ionic compounds are no longer regularly used

Chronic

In test animals, brominated vegetable oils (BVOs), historically used as emulsifiers in certain soda-based soft drinks, produced damage to the heart and kidneys in addition to increasing fat deposits in these organs. In extreme cases, BVOs caused testicular damage, stunted growth and produced lethargy and fatigue.

Brominism (chronic bromine poisoning) produces slurred speech, apathy, headache, decreased memory, anorexia and drowsiness, psychosis resembling paranoid schizophrenia, and personality changes.

Several cases of foetal abnormalities have been described in mothers who took large doses of bromides during pregnancy. Reduced breathing capacity may result from chronic low level exposure to chlorine gas. Chronic poisoning may result in cough, severe chest pains, sore throat and blood in the phlegm. Moderate to severe exposures over 3 years produced decreased lung capacity in a number of workers

Delayed effects can include shortness of breath, violent headaches, lung swelling and pneumonia.

Chloralkali workers exposed over many years showed fatigue, and a modest increase in anxiety and dizziness. There may be an increase in white blood cell and decrease in red blood cell count.

Spa Pro Bromine Tablets	TOXICITY	IRRITATION
	Not Available	Not Available
	TOXICITY	IRRITATION
1-bromo-3-chloro-5,5- dimethylhydantoin	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Primary Skin Irritation Index 6.1
	Oral (rat) LD50: 1390 mg/kg ^[2]	Skin (rabbit): SEVERE **
Legend:	Value obtained from Europe ECHA Registered Substate otherwise specified data extracted from RTECS - Regist	ances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested

No significant acute toxicological data identified in literature search.

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production

1-BROMO-3-CHLORO-5,5-DIMETHYLHYDANTOIN

Acute toxicity: The halohydantoins were shown to be of low toxicity by the oral and dermal routes of exposure. Acute toxicity by the inhalation route is more significant. The halohydantoins are significant eye and skin irritants . Dermal sensitization has also been observed for some of the halohydantoin com pounds.

Non-acute toxicity testing of halohydantoins and their breakdown products dimethylhydantoin and ethylmethylhydantoin (DMH/EMH) (including sub chronic, developmental, reproductive, and chronic toxicity testing) all show the presence of non-specific toxicity only at relatively high doses of the test chemical. The primary reason for developing generic data on DMH and EMH rather than the entire halohydantoin molecule is that these ring structures represent the persistent component of the halohydantoins. A secondary reason for evaluating the halohydantoin moieties is that the corrosive properties of the released halogens would limit the amount of chemical that could be administered to laboratory animals; thereby precluding a meaningful evaluation of the halohydantoin moieties

Developmental and reproductive toxicity data demonstrate no increase in susceptibility to the toxic effects of 5,5-dimethylhydantoin with the exception of one study, where foetal and litter effects (increased incidence of 27th presacral vertebrae) in rabbits were observed at a lower dose level than that which resulted in maternal toxicity (decreased body weight and food consumption during the dosing period) following treatment. The increase of 27th presacral vertebrae is a common variation found in rabbit developmental toxicity studies and was not considered an adverse effect. In a prenatal developmental toxicity study conducted in rabbits with 5-ethyl-5-methylhydantoin, there was no increased susceptibility of the foetuses observed.

Available metabolism data indicate that DMH and EMH are excreted unchanged in the rat.

Positive sensitiser in guinea pig skin assay ** * [Farm Chem. Handbook] ** Red for Halohydantoins

Acute Toxicity Carcinogenicity Skin Irritation/Corrosion Reproductivity Serious Eve STOT - Single Exposure Damage/Irritation

Respiratory or Skin STOT - Repeated Exposure sensitisation Mutagenicity Aspiration Hazard

Leaend:

- Data available but does not fill the criteria for classification
- Data available to make classification
- Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Spa Pro Bromine Tablets	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
1-bromo-3-chloro-5,5- dimethylhydantoin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.14mg/L	4
	EC50	48	Crustacea	0.4mg/L	4

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Chlorine:

Atmospheric Fate: Atmospheric chlorine forms hydrochloric or hypochlorous acid in the atmosphere, either through reactions with hydroxyl radicals or, other trace species, such as hydrocarbons. These acids are believed to be removed from the atmosphere primarily through precipitation washout/dry deposition. When chlorine, hypochlorous acid or hydrogen chloride mixes in the atmosphere with water vapor, dilute solutions of strong mineral acids form which fall to earth as �acid rain ♠, snow, fog, or acidified dry particles. Terrestrial Fate: Soil - Chlorine may react with soil components to form chlorides; depending on their water solubility, these chlorides are easily washed out from the soil. Plants - Vegetation acts as an important artificial reservoir, (sink), for chlorine air pollution. Elevated levels of chlorine can cause plant injury; however chlorine tends to be rapidly converted to other less toxic forms. Chlorine is toxic to plant growth, however; it is also essential to plant growth - crops need around 2 kg or more of chlorine per acre. Acute toxicity is characterized by defoliation, with no leaf symptoms and, in higher plant forms, by spotting of the leaves.

Aquatic Fate: Water chlorination initially introduces chlorine into the water as chlorine gas, hypochlorite ion, or its salt. Chlorine in aqueous systems evaporates, or quickly decays, to residual forms, such as hypochlorous acid, chloramine and/or chlorinated organics.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1-bromo-3-chloro-5,5- dimethylhydantoin	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
1-bromo-3-chloro-5,5- dimethylhydantoin	LOW (LogKOW = -0.9441)

Mobility in soil

Ingredient	Mobility
1-bromo-3-chloro-5,5- dimethylhydantoin	LOW (KOC = 23.14)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Containers may still present a chemical hazard/ danger when empty.

Return to supplier for reuse/ recycling if possible.

Otherwise:

If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in

their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Reduction

Reuse

Recycling

Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.

Product / Packaging disposal

DO NOT allow wash water from cleaning or process equipment to enter drains It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

Where in doubt contact the responsible authority

Recycle wherever possible.

Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurrying in water; Neutralisation with soda-lime or soda-ash followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)

Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

For small quantities of oxidising agent:

Cautiously acidify a 3% solution to pH 2 with sulfuric acid.

Gradually add a 50% excess of sodium bisulfite solution with stirring.

Add a further 10% sodium bisulfite.

If no further reaction occurs (as indicated by a rise in temperature) cautiously add more acid.

SECTION 14 TRANSPORT INFORMATION





Marine Pollutant



HAZCHEM

Land transport (DOT)

UN number	3085		
UN proper shipping name	OXIDISING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)		
Transport hazard class(es)	Class 5.1 Subrisk 8		
Packing group	П		
Environmental hazard	Environmentally hazardous		
Special precautions for user	Special provisions 274 Limited quantity 1 kg		

Air transport (ICAO-IATA / DGR)

UN number	3085				
UN proper shipping name	Oxidizing solid, corrosive, n.o.s. * (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)				
	ICAO/IATA Class	5.1			
Transport hazard class(es)	ICAO / IATA Subrisk	8			
	ERG Code	5C			
Packing group	II				
Environmental hazard	Environmentally hazardous				
	Special provisions		A3		
	Cargo Only Packing Instructions		562		
	Cargo Only Maximum Qty / Pack		25 kg		
Special precautions for user	Passenger and Cargo Packing Instructions		558		
	Passenger and Cargo Maximum Qty / Pack		5 kg		
	Passenger and Cargo Limited Quantity Packing Instructions		Y544		
	Passenger and Cargo	Limited Maximum Qty / Pack	2.5 kg		

Sea transport (IMDG-Code / GGVSee)

UN number	3085		
UN proper shipping name	OXIDIZING SOLID, CORROSIVE, N.O.S. (contains 1-bromo-3-chloro-5,5-dimethylhydantoin)		
Transport hazard class(es)	IMDG Class 5.1 IMDG Subrisk 8		
Packing group			
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS Number F-A , S-Q Special provisions 274		
	Limited Quantities 1 kg		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

 ${\color{red} \|}~\textbf{1-BROMO-3-CHLORO-5,5-DIMETHYLHYDANTOIN(16079-88-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS$

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (1-bromo-3-chloro-5,5-dimethylhydantoin)
China - IECSC	Υ

Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	01/06/2018
Initial Date	01/06/2018

Other information

Ingredients with multiple cas numbers

Name	CAS No
1-bromo-3-chloro-5,5- dimethylhydantoin	16079-88-2, 32718-18-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.